

PCE



Illustrative photo

XREEL250 extension cord - 4xGS output with ter.

Product No

92501T48263

See variants

XREEL250 extension cord - 4xGS output with ter.

Housing material : Plastic

Type of cable used : H05RR-F

Cable cross section : 2.5 mm²

Number of cores : 3

Number of CEE sockets : 0

Number of sockets with protective contact (type F) : 4

Number of Bipasso sockets (Italy) : 0

Number Type 13 (Swiss) sockets : 0

Number of Type 15 (Swiss) sockets : 0

Number of Type 23 (Swiss) sockets : 0

Number of Type 25 (Swiss) sockets : 0

Cord length : 30 m

With stand : Yes

Automatic cord rewind : No

With thermal protection : Yes

Degree of protection (IP) : IP20

CE

Housing material	Plastic	Cord length	30 m
Type of cable used	H05RR-F	With stand	Yes
Conductor cross-section	2.5mm ²	Automatic cord rewind	NO
Number of veins	3	With thermal protection	Yes
Number of protective contact sockets (type F)	4	Degree of protection (IP)	IP20

PCE POLSKA SP. Z O.O. | st. Podwalna 8a | 58-200 Dzierżonów | Tel. 74 831 76 00 | pce@pce.pl